




Ref. Certif. No.

SE-93509

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	ITE POWER SUPPLY
Name and address of the applicant	GlobTek Inc. 186 Veterans Drive, Northvale, NJ 07647 USA
Name and address of the manufacturer	Same as applicant
Name and address of the factory <i>Note: When more than one factory, please report on page 2</i>	See page 2
Ratings and principal characteristics	Input: 100-240V~, 50-60Hz, 1.5A Output: 5-54Vdc, Max. 8.00A, Max. 65W
Trademark (if any)	
Customer's Testing Facility (CTF) Stage used	-
Model / Type Ref.	GT*96600_*****
Additional information (if necessary may also be reported on page 2)	See page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2014
As shown in the Test Report Ref. No. which forms part of this Certificate	180702573SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 11 March 2019



Signature:

Robin Xu

Factories

GlobTek Inc.
186 Veterans Drive, Northvale, NJ 07647 USA

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76 JinLing East Road, Suzhou Industrial Park, Suzhou JiangSu, 215021, China

Additional information

Group difference for CENELEC countries and national differences USA and Canada are considered.

Explanation of model GT*96600_*****

The 1st symbol "*" can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd symbol "*" denotes the rated output wattage designation, which can be "01" to "65", with interval of 1.

The 3rd symbol "*" denote the standard rated output voltage designation, which can be "05" to "54" or "5.0" to "54.0" in 0.1V increments.

The 4th symbol "*" is Blank

The 5th symbol "*" =-T2 means desktop class II with C8 AC inlet
=-T2A means desktop class II with C18 AC inlet
=-T3 means desktop class I with C14 AC inlet
=-T3A means desktop class I with C6 AC inlet
=-T2L means desktop class II with C8 AC inlet and housing with a DC jack
=-T2AL means desktop class II with C18 AC inlet and housing with a DC jack
=-T3L means desktop class I with C14 AC inlet and housing with a DC jack
=-T3AL means desktop class I with C6 AC inlet and housing with a DC jack
=-R2 means hybrid desktop housing class II with C8 AC inlet
=-R3A means hybrid desktop housing class I with C6 AC inlet
=-P2 means Encapsulated class II
=-P3 means Encapsulated class I

The last "*" denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.

Date: 11 March 2019

Signature: